

Schroeder Process Filtration - Table of Contents

	Page
Corporate Overview	2
Introduction to Process Filtration Technology	3
Industries Served	4
Filter Selection	5
Element Selection Guide	6
Automatic Backflushing Filters	8
Backflushing Filters	
Filter	Flow Range gpm (L/min)
RF3-C	20-120 (80-470)
RF3-0	110-500 (420-1,880)
RF3-1	395-1,120 (1,500-4,235)
RF3-2	880-1,980 (3,335-7,500)
RF3-2.5	1,760-2,640 (6,670-10,000)
RF3-3	2,420-3,790 (9,170-14,350)
RF3-4	3,570-7,490 (13,500 - 28,300)
RF3-5	6,600-10,790 (25,000 - 40,850)
RF3-6	8810-15,850 (33,350-60,000)
RF3-7	13,200-22,000 (50,000-83,350)
RF3-8	19,800-33,000 (75,000-125,000)TR
RF5	748-18,480 (2,833-70,000)
RF7	22-33,022 (83-125,000)
RF4-1	32 (120)
RF4-2	60 (220)
RFH-1	106 (400)
RFH-2	160 (600)
RFH-4	210 (800)
ATF	35-1760 (133-6,662)
Bag Filtration	
BH1	100 psi (7 bar)
BH1	150 psi (10 bar)
BH2-BH10	150 psi (10 bar)
DBH2 - DBH10	150 psi (10 bar)
Bag Element Operating Guidelines	68
Bag Elements	69
Micron Rated Filter Bags	70
Oil Absorbing Bags (OAB)	71
High Efficiency Bags (PPH)	72
Absolute Efficiency Bags (PPA)	73
Cartridge Housings and Elements	
Overview	74
DCE Economical Meltblown Elements	75
ACE Absolute Meltblown Elements	76
CH1	78
CH3-CH7	100 psi (7 bar)
CH3-CH7	150 psi (10 bar)
CH12-CH24	150 psi (10 bar)
Rolling Media Filter	
RMF	70-6000 (265-2270)
Oil and Gas Products	
PPS	89
Mining Products	
Introduction	90
LW60	300 (1135)
Excellement®-MD	94
Mining Specific Elements	95
Glossary	101
Process Filtration Worksheet	102